

# CAMBRIDGE

## MODEL 680-RX AMBULATORY AND WHEELCHAIR SCALES



The Cambridge Model 680-RX includes two live hand rails, a single easy incline ramp and rear bumper safety guard. An optional second ramp assembly, as shown above, may easily be added if desired.

The 680-RX is compatible with all of the indicators manufactured by Cambridge Scale Works. Please ask your dealer to recommend which indicator best suits your application needs.



Underside view showing structural tubular steel design. Load cell position allows live side/hand rails.

### Standard Features:

- Ultra-Lo Profile Design is Only 1.5" High from Floor Level
- Live Safety Side Rails for Roll Off Protection
- Two Live Hand Rails Allow Accurate Weighing While Supporting Patients
- Smooth Deck Plate with Anti-Skid Tape for Safety
- Four Internally Mounted NTEP Certified 5,000 Division, Class III/IIIL, Environmentally Protected, IP67 Water Resistant Rated Load Cells
- One Rear Safety Bumper Rail Assembly and One Ramp
- Structural Tubular Steel Design with 100% End Loading Capacity
- Anti-Skid, Easy Access Leveling Feet
- 200% Overload Protection
- 20' Indicator Cable
- Easy Access Junction Box for Corner Adjusting
- Shielded Signal and Load Cell Cables

### Approvals:



### Members:

- THE NATIONAL CONFERENCE ON WEIGHTS AND MEASURES
- THE INTERNATIONAL SOCIETY OF WEIGHING AND MEASUREMENT



# C A M B R I D G E

## MODEL 680-RX AMBULATORY AND WHEELCHAIR SCALES

Platform Size	Overall Size	Capacity	Ship Weight
30" X 30" X 1.5"	36" X 48" including ramp	1,000 lbs. X .2 lbs.	190 lbs. including ramp
30" X 30" X 1.5"	36" X 48" including ramp	2,500 lbs. X .5 lbs.	190 lbs. including ramp
36" X 36" X 1.5"	42" X 54" including ramp	1,000 lbs. X .2 lbs.	250 lbs. including ramp
36" X 36" X 1.5"	42" X 54" including ramp	2,500 lbs. X .5 lbs.	250 lbs. including ramp
48" X 48" X 2"	54" X 72" including ramp	1,000 lbs. X .2 lbs.	415 lbs. including ramp
48" X 48" X 2"	54" X 72" including ramp	2,500 lbs. X .5 lbs.	415 lbs. including ramp

Dimensions subject to change without notice. Custom sizes and capacities available.



The Cambridge Model 680-RX ships as shown at left with two live hand rails, a single easy incline ramp and rear bumper safety guard. An optional second ramp assembly, as shown on the front of this sheet, may easily be added if desired. Match with one of our full line of Cambridge indicators for a factory calibrated Cambridge System. Please ask your dealer to recommend which indicator best suits your application needs.



The junction board is housed inside the tube of the Model: 680-RX. This arrangement protects the junction board but still allows easy access for periodic adjustments.



Each load cell is "pocketed" in the frame of the scale, thus protecting both the load cell and the wiring.



Distributed By:

Cambridge Scale Works, Inc. will warrant this product for one full year against defects in material and/or workmanship.

**Cambridge Scale Works, Inc. • P O Box 670 • Honey Brook, PA 19344  
(800) 292-7640 • (610) 273-7040 • [www.cambridgescale.com](http://www.cambridgescale.com)**