

# C A M B R I D G E

## Model: CSW-15AT Wireless Remote Control Digital Indicator with 1.5" LED Display



COC #: 06-070A1



Measurement  
Canada Approval  
# AM-5778C

<u>PART #</u>	<u>MODEL</u>	<u>DESCRIPTION</u>	<u>LIST</u>
4900-1006-00	CSW-15AT	Wireless Remote Control Digital Indicator with 1.5" LED Display	\$995.

### Specifications:

- Wireless Remote Controls
- 6 Digit 1.5" Red LED Display
- LED Annunciators
- Die Cast Aluminum Enclosure
- Stainless Steel Adjustable Stand
- 100-240 VAC Adapter, 50/60 Hz
- Load Cell Excitation for (8) 350 OHM Load Cells
- LB / KG Conversion
- RS232 Output—On Demand or Continuous
- 1-5 Points of Digital Calibration
- Span Adjustment at Increasing or Decreasing Weights
- Gross / Net / Tare
- NTEP 5,000 Divisions / NON-NTEP 20,000 Divisions
- Weight Totalization
- Keypad Calibration w/Audit Trail



### Options:

- CSW-15AT **without** wireless remote control \$850.
- 110 VAC Dry Contact Set Point \$275.
- Peak Weight Hold \$ 45.
- Digital Scroll Tare \$ 45.
- Part #: 1790-1032-00-RFL-Radio Frequency Link Consult Factory  
Includes: Transmitter and Receiver (120 VAC)
- Wi-Fi Transmitter To Customer's Wireless Hub— 802.11 B/G \$495.
- Ethernet Connection \$495.
- Scale Warning System \$375.  
(strobe light with audible alarm warns operator when set limits have been exceeded)

Effective Date: 1/01/17

Prices Subject to Change Without Notice

F.O.B. Honey Brook, PA

# C A M B R I D G E

**Model: CSW-15AT-B**

**Battery Operated Wireless Remote Control  
Digital Indicator with 1.5" LED Display**



**COC #: 06-070A1**

**Measurement  
Canada Approval  
# AM-5778C**

<u>PART #</u>	<u>MODEL</u>	<u>DESCRIPTION</u>	<u>LIST</u>
<b>4900-1019-00</b>	CSW-15AT-B	Battery Operated Wireless Remote Control Digital Indicator with 1.5" LED Display	\$1,150.

**Specifications:**

- Wireless Remote Controls
- 6 Digit 1.5" RED LED Display
- Battery Operation (Internal Rechargeable) 8 VDC, 3.2AH
- 100-240 VAC Adapter/Charger, 50/60 Hz
- Adjustable Sleep Mode
- Low Battery Indication
- LED Annunciators
- Die Cast Aluminum Enclosure
- Stainless Steel Adjustable Stand
- Load Cell Excitation for (8) 350 OHM Load Cells
- LB / KG Conversion
- RS232 Output—On Demand or Continuous
- 1-5 Points of Digital Calibration
- Span Adjustment at Increasing or Decreasing Weights
- Gross / Net / Tare
- NTEP 5,000 Divisions / NON-NTEP 20,000 Divisions
- Weight Totalization (Standard)
- Keypad Calibration w/Audit Trail



**Options:**

- Peak Weight Hold \$ 45.
- Digital Scroll Tare \$ 45.
- Part #: 1790-1032-00RFL-Radio Frequency Link- Includes: Transmitter and Receiver (120 VAC) Consult Factory
- Wi-Fi Transmitter To Customer's Wireless Hub- 802.11 B/ \$495.

**Accessories:**

- 1165-1012-00** Spare Battery—7.4 VDC 3,000 MAH \$ 60.
- 1168-1007-00** Spare Battery Charger (Wall Unit) \$ 75.

**Effective Date: 1/01/17**

**F.O.B. Honey Brook, PA**

**Prices Subject to Change Without Notice**