

C A M B R I D G E

Model: SSCSW-10AT

Stainless Steel Digital Indicator with LED Display



COC #: 06-070A1



**Measurement
Canada Approval
AM-5778C**

<u>PART #</u>	<u>MODEL</u>	<u>DESCRIPTION</u>	<u>LIST</u>
4900-1016-00	SSCSW-10AT	Stainless Steel Digital Indicator, LED Display 6 Pin Watertight Quick Disconnect	\$595.

Specifications:

- Stainless Steel NEMA IV Enclosure
- Stainless Steel Adjustable Stand
- 6 Pin Watertight Signal Connection (Quick Disconnect)
- 100-240 VAC, 50/60 Hz AC Power Cord
- .56" Red LED Display
- LED Annunciators
- 6 Digit Display
- Load Cell Excitation for (8) 350 OHM Load Cells
- LB / KG Conversion
- RS232 Output—On Demand or Continuous (Standard)
- RFI / EMI Screened
- 1-5 Points of Digital Calibration
- Span Adjustment at Increasing or Decreasing Weights
- Gross / Net / Tare
- NTEP 5,000 Divisions / NON-NTEP 20,000 Divisions
- Totalization
- Keypad Calibration w/Audit Trail



Options:

- 110 VAC Dry Contact Set Point \$275.

Effective Date: 1/01/17

Prices Subject to Change Without Notice

F.O.B. Honey Brook, PA

C A M B R I D G E

Model: SSCSW-10AT-B

Stainless Steel Battery Operated Digital Indicator with LED Display



COC #: 06-070A1



**Measurement
Canada Approval
AM-5778C**

<u>PART #</u>	<u>MODEL</u>	<u>DESCRIPTION</u>	<u>LIST</u>
4900-1021-00	SSCSW-10AT-B	Battery Operated Stainless Steel Digital Indicator, LED Display 6 Pin Watertight Quick Disconnect	\$745.

Specifications:

- Battery Operation (Internal Rechargeable) 8 VDC, 3.2 AH
- Stainless Steel NEMA IV Enclosure w/S.S. Adjustable Stand
- 6 Pin Watertight Signal Connection (Quick Disconnect)
- 100-240 VAC, 50/60 Hz AC Power Cord
- 6 Digit .56" Red LED Display
- LED Annunciators
- Load Cell Excitation for (8) 350 OHM Load Cells
- LB / KG Conversion
- RS232 Output—On Demand or Continuous (Standard)
- RFI / EMI Screened
- Internal Battery Charger
- Low Battery Indication
- Adjustable Sleep Mode
- 1-5 Points of Digital Calibration
- Span Adjustment at Increasing or Decreasing Weights
- Gross / Net / Tare
- NTEP 5,000 Divisions / NON-NTEP 20,000 Divisions
- Weight Totalization
- Keypad Calibration w/Audit Trail



Options:

- Peak Weight Hold \$ 45.
- Digital Scroll Tare \$ 45.

Spare Parts:

- 1165-1012-00** Spare Battery—7.4 VDC 3,000 MAH \$ 60.

Effective Date: 1/01/17

Prices Subject to Change Without Notice

F.O.B. Honey Brook, PA