BRID

MODEL SA610-B-SS-10AT SERIES **BENCH SCALES**



- · SSCSW-10AT check weighing indicator.
- 5 lb. to 500 lb. capacity.
- · High strength cast aluminum subframe.
- · Stainless steel hardware.
- · Heavy gauge stainless steel cover.
- · IP 65 water seal rated aluminum load cell.
- Overload and corner protection.
- Four vibration absorbant anti-skid, stainless steel leveling feet.
- · Rubber anti-vibration shock mounts.
- · Meets NIST HB-44 requirements for class III, 5000 division.
- · 20" stainless steel column with 4" X 8" indicator mounting plate.

Model SA610-B with stainless steel cover removed showing high strength cast aluminum subframe, overload protection, rubber anti-vibration shock mounts and stainless steel indicator column with mounting plate.

CAMBRIDGE

· INCLUDES:

SSCSW-10AT check weighing indicator.











MODEL SA610-B-SS-10AT SERIES BENCH SCALES

Model SA610-B-SS-10AT Specifications				
PLATFORM SIZE	CAPACITY	LOAD CELL	APPROX. SHIPPING WEIGHT	
12" x 12" x 3.5"	10 lb.	10 Kg.	39 lb.	
	25 lb.	20 Kg.	39 lb.	
	50 lb.	50 Kg.	39 lb.	
	100 lb.	75 Kg.	39 lb.	
	200 lb.	100 Kg.	39 lb.	
13" x 18" x 3.5"	10 lb.	10 Kg.	42 lb.	
	25 lb.	20 Kg.	42 lb.	
	50 lb.	50 Kg.	42 lb.	
	100 lb.	75 Kg.	42 lb.	
	200 lb.	100 Kg.	42 lb.	
18" x 18" x 4.5"	50 lb.	50 Kg.	61 lb.	
	100 lb.	100 Kg.	61 lb.	
	250 lb.	250 Kg.	61 lb.	
	500 lb.	500 Kg.	61 lb.	





Model SSCSW-10AT Standard Features Include:

- Stainless Steel NEMA 4X Enclosure with Stainless Steel Swivel Stand
- Selectable: NTEP 5,000 Divisions Non-NTEP 20,000 Divisions
- Net/Gross Display Modes
- Full Range Auto Tare
- · Adjustable Digital Filtering
- All Pushbutton Controls
- · LED Display (Bright)
- Printer Data Output on Demand
- Clearly, Visible Center of Zero Indication on Display
- Keypad Calibration with Audit Trail
- Weight Totalization

- Lb/Kg Conversion
- 1 to 5 Points of Digital Calibration
- Span Adjustment at Increasing or Decreasing Weights
- · Full Range Push Button Zero
- (1) RS-232 Port for Interface with:
 - · Printer Output of Gross/Tare/Net
 - · Computer Data Output
- Scoreboard Continuous Output Alphanumeric or Numeric
- 100-240 VAC, 50/60 Hz Power Cord
- Auto Zero Tracking
- Adjustable Motion Detection
- (6) Pin Water-Tight Signal Connection
- Check Weighing

Cambridge Scale Works, Inc. will warrant this product for one full year against defects in material and/or workmanship.