

C A M B R I D G E

Model: CSW-15AT Wireless Remote Control Digital Indicator with 1.5" LED Display



COC #: 06-070A1



Measurement
Canada Approval
AM-5778C

<u>PART #</u>	<u>MODEL</u>	<u>DESCRIPTION</u>	<u>LIST</u>
4900-1006-00	CSW-15AT	Wireless Remote Control Digital Indicator with 1.5" LED Display	\$1,095.

Specifications:

- Wireless Remote Controls
- 6 Digit 1.5" Red LED Display
- LED Annunciators
- Die Cast Aluminum Enclosure
- Stainless Steel Adjustable Stand
- 100-240 VAC Adapter, 50/60 Hz
- Load Cell Excitation for (8) 350 OHM Load Cells
- LB / KG Conversion
- RS232 Output—On Demand or Continuous
- 1-5 Points of Digital Calibration
- Span Adjustment at Increasing or Decreasing Weights
- Gross / Net / Tare
- NTEP 5,000 Divisions / NON-NTEP 20,000 Divisions
- Weight Totalization
- Keypad Calibration w/Audit Trail



Options:

- CSW-15AT **without** wireless remote control \$935.
- 110 VAC Dry Contact Set Point \$295.
- Peak Weight Hold \$ 45.
- Digital Scroll Tare \$ 45.
- Part #: 1790-1032-00-RFL-Radio Frequency Link Consult Factory
Includes: Transmitter and Receiver (120 VAC)
- Wi-Fi Transmitter To Customer's Wireless Hub— 802.11 B/G \$495.
- Ethernet Connection \$495.
- Scale Warning System \$395.
(strobe light with audible alarm warns operator when set limits have been exceeded)

Effective Date: 1/01/20

Prices Subject to Change Without Notice

F.O.B. Honey Brook, PA

C A M B R I D G E

Model: CSW-15AT-B

Battery Operated Wireless Remote Control Digital Indicator with 1.5" LED Display



COC #: 06-070A1



Measurement
Canada Approval
AM-5778C

<u>PART #</u>	<u>MODEL</u>	<u>DESCRIPTION</u>	<u>LIST</u>
4900-1019-00	CSW-15AT-B	Battery Operated Wireless Remote Control Digital Indicator with 1.5" LED Display	\$1,265.

Specifications:

- Wireless Remote Controls
- 6 Digit 1.5" RED LED Display
- Battery Operation (Internal Rechargeable) 8 VDC, 3.2AH
- 100-240 VAC Adapter/Charger, 50/60 Hz
- Adjustable Sleep Mode
- Low Battery Indication
- LED Annunciators
- Die Cast Aluminum Enclosure
- Stainless Steel Adjustable Stand
- Load Cell Excitation for (8) 350 OHM Load Cells
- LB / KG Conversion
- RS232 Output—On Demand or Continuous
- 1-5 Points of Digital Calibration
- Span Adjustment at Increasing or Decreasing Weights
- Gross / Net / Tare
- NTEP 5,000 Divisions / NON-NTEP 20,000 Divisions
- Weight Totalization (Standard)
- Keypad Calibration w/Audit Trail



Options:

- Peak Weight Hold \$ 45.
- Digital Scroll Tare \$ 45.
- Part #: 1790-1032-00RFL-Radio Frequency Link- Consult Factory
Includes: Transmitter and Receiver (120 VAC)
- Wi-Fi Transmitter To Customer's Wireless Hub- 802.11 B/ \$495.

Accessories for Indicators with a Serial Number BEFORE 20552-17:

- 1165-1012-00 Spare Battery—7.4 VDC 3,000 MAH \$ 66.
- 1168-1007-00 Spare Battery Charger (Wall Unit) \$ 72.

Accessories for Indicators with a Serial Number 20552-17 and AFTER:

- 1165-1030-00 Spare Battery—3.7 VDC 3,200 MAH \$ 33.
(2 Required per Indicator, price is per battery)
- 1168-1015-00 Spare Battery Charger (External) \$ 76.

Effective Date: 1/01/20

F.O.B. Honey Brook, PA

Prices Subject to Change Without Notice