

C A M B R I D G E

Model: SSCSW-10AT

Stainless Steel Digital Weight & Check Weighing Indicator



COC #: 06-070A1



Measurement
Canada Approval
AM-5778C

<u>PART #</u>	<u>MODEL</u>	<u>DESCRIPTION</u>	<u>LIST</u>
4900-1016-00	SSCSW-10AT	Stainless Steel Digital Indicator, (6) Pin Watertight Quick Disconnect *Includes Check Weighing Feature	\$650.

Specifications:

- Stainless Steel NEMA IV Enclosure
- Stainless Steel Adjustable Stand
- 6 Pin Watertight Signal Connection (Quick Disconnect)
- 100-240 VAC, 50/60 Hz AC Power Cord
- .56" Red LED Display
- LED Annunciators
- 6 Digit Display
- Load Cell Excitation for (8) 350 OHM Load Cells
- LB / KG Conversion
- RS232 Output—On Demand or Continuous (Standard)
- RFI / EMI Screened
- 1-5 Points of Digital Calibration
- Span Adjustment at Increasing or Decreasing Weights
- Gross / Net / Tare
- NTEP 5,000 Divisions / NON-NTEP 20,000 Divisions
- Totalization
- Keypad Calibration w/Audit Trail
- Check Weighing



Options:

- 110 VAC Dry Contact Set Point \$295.
- Peak Weight Hold \$ 45.
- Digital Scroll Tare \$ 45.
- Wi-Fi Transmitter to customer's wireless hub- 802.11 B/G \$495.
- Ethernet Connection \$495.
- Scale Warning System (NEMA IV) \$395.

Effective Date: 1/01/19

Prices Subject to Change Without Notice

F.O.B. Honey Brook, PA

C A M B R I D G E

Model: SSCSW-10AT-B

Stainless Steel AC/Battery Operated Digital Weight & Check Weighing Indicator



COC #: 06-070A1



Measurement

Canada Approval

AM-5778C

<u>PART #</u>	<u>MODEL</u>	<u>DESCRIPTION</u>	<u>LIST</u>
4900-1021-00	SSCSW-10AT-B	Battery Operated Stainless Steel Digital Indicator LED Display, 6 Pin Watertight Quick Disconnect *Includes Check Weighing Feature	\$795.

Specifications:

- Battery Operation (Internal Rechargeable) 8 VDC, 3.2 AH
- Stainless Steel NEMA IV Enclosure w/S.S. Adjustable Stand
- 6 Pin Watertight Signal Connection (Quick Disconnect)
- 100-240 VAC, 50/60 Hz AC Power Cord
- 6 Digit .56" Red LED Display
- LED Annunciators
- Load Cell Excitation for (8) 350 OHM Load Cells
- LB / KG Conversion
- RS232 Output—On Demand or Continuous (Standard)
- RFI / EMI Screened
- Internal Battery Charger
- Low Battery Indication
- Adjustable Sleep Mode
- 1-5 Points of Digital Calibration
- Span Adjustment at Increasing or Decreasing Weights
- Gross / Net / Tare
- NTEP 5,000 Divisions / NON-NTEP 20,000 Divisions
- Weight Totalization
- Keypad Calibration w/Audit Trail
- Check Weighing



Options:

- | | |
|-----------------------|-------------|
| • Peak Weight Hold | <u>LIST</u> |
| • Digital Scroll Tare | \$ 45. |
| | \$ 45. |

Spare Parts:

- | | | |
|--------------|--|--------|
| 1705-1073-00 | Power cable—AC Cord with Cable Connector | \$ 98. |
|--------------|--|--------|

Accessories for Indicators with a Serial Number BEFORE 20552-17:

- | | | |
|--------------|---------------------------------|--------|
| 1165-1012-00 | Spare Battery—7.4 VDC 3,000 MAH | \$ 66. |
|--------------|---------------------------------|--------|

Accessories for Indicators with a Serial Number 20552-17 and AFTER:

- | | | |
|--------------|---|--------|
| 1165-1030-00 | Spare Battery—7.4 VDC 3,000 MAH
(2 Required per Indicator, price is per battery) | \$ 33. |
|--------------|---|--------|

Effective Date: 1/01/20

Prices Subject to Change Without Notice

F.O.B. Honey Brook, PA